Six-Position Contact Charging Plate

Jian Bian Lighting | JBTD-160 project family | English public edition | 20 October 2026

Specification summary

This summary translates the supplied product information. It is not an approved engineering specification or a test report. Confirm the final six-position configuration and sample before ordering.

Item	Source-stated information and confirmation status
Product	Six-position contact charging plate
Dimensions	460 x 310 x 25 mm. Source-stated; verify against the final sample.
Per-position rating	5 V DC, 1 A per compatible lamp / position (5 W nominal). Owner-confirmed on 9 October 2026.
Adapter information	Source states: 50 W; three-pin AC inlet; DC 5 V, 10 A; 5.5 x 2.5. Confirm the adapter model, inlet/plug, connector dimensions and whether the adapter is included.
Charging interface	DC as stated in the source. Exact contact layout, polarity and compatible lamp models require engineering confirmation.
Nominal load calculation	6 x 5 W = 30 W nominal connected-lamp load. This is a calculation, not measured input power, charging speed or efficiency.

Not established by the source

Included lamps; simultaneous charging test results; universal compatibility; certifications; warranty; price; MOQ; lead time; material; net weight; and packaging remain unconfirmed. No claims are made for these fields.

Before publication or purchase

Obtain engineering approval for the exact six-position plate and compatible lamps. Do not substitute information from the separate 33-position charging trolley.

Editorial note: the Chinese source-table screenshot is omitted from this public English edition. The original source is retained internally; this translation does not replace engineering verification.

Product enquiries: https://jianbianlighting.com.cn/contact/